



Can

SUITABLE FOR BMC APPLICATION



ANTI FRICTION MOVEMENT
ROUND THE GLOBE



Can Bearing No.	O.E.M	Bore Dia(mm)	Outer Dia(mm)	Total Bearing Height(mm)	Illustration
32010		50.000	80.000	20.000	
32013		65.000	100.000	23.000	
6379/6320	13R5 24948 281036 40004150 5539Z110 69002	65.090	135.760	53.980	
CAN88730001	15W65	0.000	0.000	0.000	
CAN88730002	582778/PRO822	0.000	0.000	0.000	
CAN88730003	582778/PRO620	0.000	0.000	0.000	
RMS9 RS	YF3534	28.575	71.438	20.640	
RMS9-2RS	226300	28.575	71.438	20.640	
RMS9-ZZ	6K528	28.575	71.438	20.640	



V. Kan. Export

AN ISO/TS 16949:2009 CERTIFIED CO.

WORKS: PLOT NO.: 347, SECTOR-8, IMT-MANESAR, GURUGRAM-122050, HARYANA (INDIA)
TELEFAX: +91-124-406-7421, +91-9810049380, +91-9810099961
E.MAIL : canbearing@gmail.com , vaibhav.ahuja82@gmail.com

www.canbearings.com