



Can

CLARK



ANTI FRICTION MOVEMENT
ROUND THE GLOBE



Can Bearing No.	O.E.M	Bore Dia(mm)	Outer Dia(mm)	Total Bearing Height(mm)	Illustration
1380/1328		22.230	52.390	19.370	
15101/15250		25.400	63.500	20.640	
212049/212011		66.675	122.238	38.100	
26882/26822		41.280	79.380	23.810	
2788/2726		0.000	0.000	0.000	
304 KRR2	941112	20.000	52.000	28.070	
48190/48120		107.950	161.930	34.930	
56418/56650		106.360	165.100	36.510	
5836	1091410089/027	43.600	64.200	13.100	
5838	1091410089/0027	43.600	69.800	23.300	
593/592		88.900	152.400	39.688	
67388/67322		0.000	0.000	0.000	

67390/67320		0.000	0.000	0.000	
67782/67720		0.000	0.000	0.000	
67883/67820		0.000	0.000	0.000	
685/672		0.000	0.000	0.000	
71450/71750		0.000	0.000	0.000	
734449/734410		0.000	0.000	0.000	
840449/840410		0.000	0.000	0.000	
898/892		0.000	0.000	0.000	



V. Kan. Export

AN ISO/TS 16949:2009 CERTIFIED CO.

WORKS: PLOT NO.: 347, SECTOR-8, IMT-MANESAR, GURUGRAM-122050, HARYANA (INDIA)
TELEFAX: +91-124-406-7421, +91-9810049380, +91-9810099961
E.MAIL : canbearing@gmail.com , vaibhav.ahuja82@gmail.com

www.canbearings.com