



Can

**SUITABLE FOR
EATON APPLICATION**



ANTI FRICTION MOVEMENT
ROUND THE GLOBE




Can Bearing No.	O.E.M	Bore Dia(mm)	Outer Dia(mm)	Total Bearing Height(mm)	Illustration
212044/212011		60.330	122.240	38.100	
212049/212011		66.675	122.238	38.100	
218248/218210		89.975	146.975	40.000	
221442/221410		0.000	0.000	0.000	
224340/224310		0.000	0.000	0.000	
25580/25523		44.450	82.930	26.990	
25581/25520	654137 / 654166 654137/654166 K-3919	44.450	82.931	23.812	
25590/25522	1313645 / 791943 1313645/791943	45.620	83.060	23.880	
25877/25821	675246 / 672070 675246/672070	34.930	73.030	23.812	
29585/29520		63.500	107.950	25.400	
33208	3094303 X8875587	40.000	80.000	32.000	
33281/33462		71.440	117.480	30.160	

33287/33462		73.030	117.480	30.160	
3782/3720	658981/660181 660181 / 658981	44.450	93.264	30.162	
394/392		0.000	0.000	0.000	
39585/39520		63.500	112.710	30.160	
39590/39520	675250 / 742259 742259/675250 K-4152	66.680	112.710	30.160	
3979/3920		57.150	112.710	30.160	
3982/3920		63.500	112.713	30.162	
3984/3920		66.680	112.712	30.162	
42688/42620		76.200	127.000	30.162	
45285/45220	711123	50.800	104.780	30.162	
47686/47620		82.550	133.350	33.340	
47687/47620		82.550	133.350	29.000	
48548/48510	X-11320	34.930	65.090	18.034	

518445/518410		88.900	152.400	39.690	
518713		45.000	112.710	35.000	
527/522		44.450	101.600	34.930	
528/522		47.630	101.600	34.930	
557/553		0.000	0.000	0.000	
567/563		73.300	127.000	36.512	
5760/5735		0.000	0.000	0.000	
580/572		82.550	139.992	36.512	
593/592		88.900	152.400	39.688	
594/592		95.250	152.400	39.688	
595/592		82.550	139.990	36.510	
598/592A		92.075	152.400	39.688	
6204	81547	20.000	47.000	14.000	

6213	81549	65.000	120.000	23.000	
6308	81511	40.000	90.000	23.000	
637/633		0.000	0.000	0.000	
643/632		69.850	136.530	41.280	
643/633		69.385	130.180	41.280	
6461/6420		76.200	149.230	53.980	
65390/65320		82.550	161.930	53.970	
6580/6535		88.900	161.930	53.980	
663/653		82.550	146.050	41.280	
665/653	665/653	85.730	146.050	42.350	
665/663		0.000	0.000	0.000	
749/742		85.030	150.090	44.450	
759/752		88.900	161.930	47.630	

760/752		90.490	161.930	47.630	
780/772		0.000	0.000	0.000	
782/772		0.000	0.000	0.000	
896/892		0.000	0.000	0.000	
CA-153	G 33149 G 33149	63.500	103.300	22.000	
CANF 17043 K	3315722	65.000	70.000	20.000	
CANF 17044 K	3315703	70.000	76.000	20.000	
CANF 17045 K	3315737	50.000	55.000	20.000	
CANF 17046 K	4124075	55.000	60.000	20.000	
CANF 17106 K	3315674	40.000	48.000	20.000	
CANF 17109 K	4304555	55.000	60.000	30.000	
CANF 17114 K	15045	25.400	33.340	25.400	
NP022333		0.000	0.000	0.000	

NP417549		0.000	0.000	0.000	
NUP213N	184571 X8872593	65.000	120.000	23.000	



V. Kan. Export

AN ISO/TS 16949:2009 CERTIFIED CO.

WORKS: PLOT NO.: 347, SECTOR-8, IMT-MANESAR, GURUGRAM-122050, HARYANA (INDIA)
TELEFAX: +91-124-406-7421, +91-9810049380, +91-9810099961
E.MAIL : canbearing@gmail.com , vaibhav.ahuja82@gmail.com

www.canbearings.com