



Can

**SUITABLE FOR  
FRUEHAUF APPLICATION**



ANTI FRICTION MOVEMENT  
ROUND THE GLOBE



Can Bearing No.	O.E.M	Bore Dia(mm)	Outer Dia(mm)	Total Bearing Height(mm)	Illustration
210249/212011		0.000	0.000	0.000	
218248/218210	M003168	89.975	146.975	40.000	
32208		40.000	80.000	24.750	
32210		50.000	90.000	24.750	
32220		100.000	180.000	49.000	
32222		110.000	200.000	56.000	
32224		120.000	215.000	61.500	
32310		50.000	110.000	42.250	
32314		70.000	150.000	54.000	
33116		80.000	130.000	37.000	
33117		85.000	140.000	41.000	
33118		90.000	150.000	45.000	

33208		40.000	80.000	32.000	
33213		65.000	120.000	41.000	
33215		75.000	130.000	41.000	
506348/506310		0.000	0.000	0.000	
518445/518410	AJA 0813 001 AJA0813 001	88.900	152.400	39.690	
524850		80.000	130.000	35.000	
593/592		88.900	152.400	39.688	
718149/718110		90.000	145.000	35.000	
BTF-0135	09400544	68.000	172.000	115.000	
VKHB2205	T6015000D000	80.000	130.000	35.000	



# V. Kan. Export

AN ISO/TS 16949:2009 CERTIFIED CO.

WORKS: PLOT NO.: 347, SECTOR-8, IMT-MANESAR, GURUGRAM-122050, HARYANA (INDIA)  
TELEFAX: +91-124-406-7421, +91-9810049380, +91-9810099961  
E.MAIL : [canbearing@gmail.com](mailto:canbearing@gmail.com) , [vaibhav.ahuja82@gmail.com](mailto:vaibhav.ahuja82@gmail.com)

[www.canbearings.com](http://www.canbearings.com)