



Can



**SUITABLE FOR  
TAFE APPLICATION**



ANTI FRICTION MOVEMENT  
ROUND THE GLOBE



Can Bearing No.	O.E.M	Bore Dia(mm)	Outer Dia(mm)	Total Bearing Height(mm)	Illustration
11949/11910		19.050	45.524	15.494	
15123/15245		31.750	62.000	18.160	
1888180 W/C	2651 2560 3101	63.500	103.400	38.200	
25877/25821		34.930	73.030	23.812	
32207		35.000	72.000	24.250	
32213		65.000	120.000	32.750	
3984/3920		66.680	112.712	30.162	
462A/453	MF1035	57.150	104.780	30.160	
48548/48510		34.930	65.090	18.034	
6202-Z		15.000	35.000	11.000	
6206		30.000	62.000	16.000	
6208-Z		40.000	80.000	18.000	
903249/10		44.450	95.250	30.960	
CAN-1310	0892862M03	63.500	102.000	20.600	
CAN-45 TF		56.300	105.000	48.700	
CAN-FE45 9W		63.500	103.500	22.500	

CAN-KAN-306497		63.500	103.400	38.200	
JC8002		30.000	62.000	19.100	



# V. Kan. Export

AN ISO/TS 16949:2009 CERTIFIED CO.

WORKS: PLOT NO.: 347, SECTOR-8, IMT-MANESAR, GURUGRAM-122050, HARYANA (INDIA)  
TELEFAX: +91-124-406-7421, +91-9810049380, +91-9810099961  
E.MAIL : [canbearing@gmail.com](mailto:canbearing@gmail.com) , [vaibhav.ahuja82@gmail.com](mailto:vaibhav.ahuja82@gmail.com)

[www.canbearings.com](http://www.canbearings.com)