






Can

SUITABLE FOR MITSUBISHI APPLICATION




ANTI FRICTION MOVEMENT
ROUND THE GLOBE



Can Bearing No.	O.E.M	Bore Dia(mm)	Outer Dia(mm)	Total Bearing Height(mm)	Illustration
0506F		25.000	62.000	19.000	
2895/28921		62.738	100.000	25.400	
30207		35.000	72.000	18.250	
30210		50.000	90.000	21.750	
30211		55.000	100.000	22.750	
30212		60.000	110.000	23.750	
32207		35.000	72.000	24.250	
803149/803110		44.450	88.900	30.162	
803149/803112		44.450	92.080	30.160	
CAN118		0.000	0.000	0.000	
CAN143		0.000	0.000	0.000	
CAN189		0.000	0.000	0.000	

CAN279		0.000	0.000	0.000	
CAN280		0.000	0.000	0.000	
CAN281		0.000	0.000	0.000	
CAN283		0.000	0.000	0.000	
DAC40740036/34		40.000	74.000	36.000	
DAC40800036/34		40.000	80.000	34.000	
RCTS 371SA1		37.000	74.000	43.000	



V. Kan. Export

AN ISO/TS 16949:2009 CERTIFIED CO.

WORKS: PLOT NO.: 347, SECTOR-8, IMT-MANESAR, GURUGRAM-122050, HARYANA (INDIA)
TELEFAX: +91-124-406-7421, +91-9810049380, +91-9810099961
E.MAIL : canbearing@gmail.com , vaibhav.ahuja82@gmail.com

www.canbearings.com